



L'huile des records du monde

AGRIPRO MULTI 4 – SAE 15W-40

Multifunctional lubricant for agricultural vehicles

USES

Lubricates the engine (supercharged or not), the transmissions, the hydraulic systems, clutch and immersed brake systems of **agricultural vehicles**.

According to the manufacturers' recommendations, use this product or a specific oil for the engine (TRANSPRO) and a special oil for the hydraulic system and the transmissions (AGRIPRO HJD or AGRIPRO HF 6).

MAIN CHARACTERISTICS

	Units	SAE 15W-40
Density at 20° C	Kg/m ³	885
Kinematic viscosity at 40° C	mm ² /s	106
Kinematic at 100° C	mm ² /s	14,2
Viscosity index		136
Pour point	° C	-30
Flash point Cleveland open cup	° C	230

The data given in this table are typical values from production and cannot be specifications in any case.

PROPERTIES & ADVANTAGES

- **Outstanding oxidation resistance** provides increased oil stability throughout the service period
- **Excellent protection** against rust, corrosion and wear
- **Friction coefficient adapted** to clutches and oil immersed brakes
- **Multigrade** capabilities maintain an adequate viscosity at hot and cold temperatures

PERFORMANCES

MULTIFUNCTIONAL (STOU)

John Deere J27 & Ford M2C 159B/C
Massey Ferguson M 1144 and M 1139
(exceeds M 1139)

TRANSMISSIONS

API GL4 - Allison C4

ENGINE

API CF-4/SF

HYDRAULICS & UTTO

HV 100 - John Deere J20C
Massey Ferguson M1135

