



L'huile des records du monde

## LUBE O - SAE 5W-30

Synthetic oil for Diesel and gasoline engines.

**"Low SAPS" technology**

### APPLICATIONS

Specifically developed for the passenger cars, the SUVs and the light commercial vehicles of the GM OPEL group requiring a **long life dexos2™ oil**.

This new standard replaces the former **GM-LL-A-025** (gasoline engines) and **GM-LL-B-025** (Diesel engines) specifications ; consequently, YACCO LUBE O is suitable for most of the GM OPEL group vehicles.

LUBE O 5W30 is also recommended for any Diesel or gasoline engines requiring one of the below specifications.

### MAIN PHYSICAL DATA

		Units	5W-30
Density at	20° C	kg/m <sup>3</sup>	849
Kinematic viscosity at	40° C	mm <sup>2</sup> /s	67
Kinematic viscosity at	100° C	mm <sup>2</sup> /s	11.7
Viscosity index			171
Flash point Cleveland open cup		° C	234
Pour point		° C	- 36
Dynamic viscosity at	- 30° C	mPa.s	6200

The data given in this table are typical production values and cannot be considered as specifications.

### PROPERTIES & ADVANTAGES

**"Low SAPS" technology (lower levels of sulphated ashes, Sulphur and Phosphorous)**

→ Extends the particle filters lifetime on Diesel engines

→ Optimal efficiency of the catalytic converters

**Reduction of fuel consumption during the whole service life of the lubricant**

→ Helps protecting the environment and reduces polluting emissions.

**Outstanding resistance to oxidation and better protection against wear**

→ Safely extended oil drain intervals

**Full compatibility with the former GM-LL-A-025 (gasoline engines) and GM-LL-B-025 (Diesel engines) specifications**

→ Use of a single engine oil for both the latest and the older vehicles.

**High shear resistance**

→ Maintains optimal oil viscosity in service

### APPROVALS

### SPECIFICATIONS



Licence dexos 2™ n° RB2A1008017

(exceeds GM-LL-A-025/GM-LL-B-025)

*Our dexos2™ licence n° RB2A1008017 is valid on service for any type of Diesel and gasoline engines of the GM-Opel group in Europe. An exhaustive list of those countries is available upon request.*

ACEA C3, API SM/CF, API SL/CF  
BMW Longlife-04, MB 229.51/MB 229.31  
VW 502.00/505.00/505.01

