



L'huile des records du monde

GALAXIE - SAE 15W-50

100% synthetic oil - for competition engines

USES

Specially formulated to meet the **modern competition engines** requirements. Particularly recommended for highly stressed Gasoline sports performance engines (turbocharged, multivalved). Suitable for catalytic converters and for turbo Diesel engines.

MAIN PHYSICAL DATA

		Units	15W-50
Density at	20° C	kg/m ³	854
Kinematic viscosity at	40° C	mm ² /s	125
Kinematic viscosity at	100° C	mm ² /s	18,3
Viscosity index			164
Pour point		° C	- 46
Flash point Cleveland open cup		°C	224
Dynamic viscosity at	- 20°C	mPa.s	4000

The data given in this table are typical values from production and cannot be specifications in any case.

PROPERTIES & ADVANTAGES

- **Excellent stability of the oil film** at hot temperature
- Outstanding detergent-dispersant properties
- Maintains the **original performances** of the engine.
- **Stable oil pressure** at hot temperature
- **Optimal protection** against deposit formation
- Formulation based upon synthetic **esters** provides increased resistance to volatility.

PERFORMANCES

GALAXIE exceeds the requirements of the major OEM, and the recommendations of the API SL/CF and ACEA A3/B4 classifications.