



L'huile des records du monde

VX 1500 - SAE 0W-30

100 % Synthetic fuel economy oil for performing Gasoline and Diesel engines

USES

100% synthetic oil for significant reduction of fuel consumption and reduction of CO₂ emissions. For passenger cars Gasoline and Diesel engines, including Direct Injection and turbocharged. Particularly recommended when the manufacturer specifies the use of SAE 0W-30 and ACEA A5/B5, ACEA A1/B1 or API SL oils: Volvo, Mitsubishi, Land Rover, Honda, Jaguar ...

MAIN PHYSICAL DATA

		Units	0W-30
Density at	20° C	kg/m ³	845
Kinematic viscosity at	40° C	mm ² /s	55
Kinematic viscosity at	100° C	mm ² /s	10
Viscosity index			171
Flash point Cleveland open cup		° C	> 220
Pour point		° C	- 54
Dynamic viscosity at	- 35° C	mPa.s	5500

The datas given in this table are typical values from production and cannot be specifications in any case.

PROPERTIES & ADVANTAGES

- 100% synthetic formula for a **perfect thermal behaviour**
 - ➔ Good lubrication in all driving conditions: road, highway, city traffic. Allows extended drain interval.
- **Low HTHS viscosity at 150°C** (high temperature viscosity under high shear)
 - ➔ Helps preserving the environment by allowing fuel economy and reducing exhaust emissions
- Excellent behaviour **in cold conditions** (100% synthetic SAE 0W-30 oil)
 - ➔ Provides instant and efficient lubrication at start-ups, reducing engine wear

SPECIFICATIONS

ACEA A5/B5
(Exceeds ACEA A1/B1)

API SL/CF

VX 1500 SAE 0W-30 meets and even exceeds the performances required by API and ACEA.