



L'huile des records du monde

VX 2000 - SAE 0W-30

100% synthetic "longlife" and fuel economy oil for very high performing Gasoline and Diesel engines

USES

Exclusively formulated to cover the most stringent requirements of both recent Gasoline and Diesel engines (since 2000) with WIV (long interval between 2 oil drains) of VW group (Audi, Seat, Skoda, Volkswagen) which request VW 503.00 standard (Gasoline), VW 506.00 standard (Diesel) or VW 506.01 standard (pump injector Diesel).

Suitable for turbocharged engines (including new Diesel direct injection technologies), multivalves, with a catalytic converter, **when the manufacturer requires an ACEA A5/B5 or ACEA A1/B1 lubricant.** Can be used in **the most difficult operating conditions** (motorways, dense city traffic,...), whatever the season.

MAIN PHYSICAL DATA

		Units	0W-30
Density at	20° C	kg/m ³	853
Kinematic viscosity at	40° C	mm ² /s	53
Kinematic viscosity at	100° C	mm ² /s	9.6
Viscosity index			167
Pour point		° C	- 54
Flash point Cleveland O.C.		° C	223
Dynamic viscosity at	- 35° C	mPa.s	< 6200

The data given in this table are typical values from production and cannot be specifications in any case.

PROPERTIES & ADVANTAGES

- Exceptional resistance to **oxidation** to keep the oil properties in duration
- Perfect **fluidity** at low temperature
- Optimal **protection** of mechanical parts
- Significant **fuel consumption reduction**
- Satisfies the most stringent OEM maintainancy conditions (**extended drain intervals**)
- Ensures **easy cold starts** while maintaining a very resistant oil film even at high temperature
- Fully preserves **the engine power**, though contributing to its youth and strenght
- Contributes to **protect the environment** by reducing the CO₂ emissions and particles

SPECIFICATIONS

VW 503.00 (Gasoline)/ **VW 506.00** (Diesel) / **VW 506.01** (Injector-pump Diesel)

ACEA A5/B5-04

VX 2000 exceeds the "longlife" requirements of Gasoline and Diesel engines of VW group, including the pump injector Diesel engines and the ACEA requirements.

For recent engines with particulate filters (DPF) which request a VW 504.00 / 507.00 oil, use YACCO VX 2103 FAP 5W-30.

