



L'huile des records du monde

VX 500 R - SAE 10W-40

Semi-synthetic oil for high performance Gasoline and Diesel engines

USES

Top range semi-synthetic engine oil for high performing Gasoline and Diesel engines.

Specific formulation for long drain intervals in Gasoline Atmospheric Renault engines.

Suitable to any type of driving conditions (long highways courses or downtown, engines doing frequent stop and go).

MAIN PHYSICAL DATA

		Units	10W-40
Density at	20° C	kg/m ³	869
Kinematic viscosity at	40° C	mm ² /s	100
Kinematic viscosity at	100° C	mm ² /s	15.0
Viscosity index			157
Flash point Cleveland open cup		°C	232
Pour point		°C	- 30
Dynamic viscosity at	- 25° C	mPa.s	6500

The data given in this table are typical values from production and cannot be specifications in any case.

PROPERTIES & ADVANTAGES

- SAE 10W grade **improves lubrication at low temperatures**
- **Semi-synthetic formulation provides excellent thermal performance** and prevents the formation of sludge deposit.
- **Good resistance to oxidation** maintains lubricating properties even for extended oil drain intervals.
- Good **detergent and dispersant** properties.

HOMOLOGATIONS

Renault RN0700
MB-Approval 229.1
VW 505.00

SPECIFICATIONS

ACEA A3/B4
API SL/CF

VX 500 R 10W40 exceeds widely the most severe performances of the main European manufacturers and the performances required by API and ACEA.

