



L'huile des records du monde

# ATF D

## Automatic transmission fluid

### USES

Lubricating fluid for automatic transmissions, semi-automatic transmissions, torque converters and power steering when the DEXRON II D specification is required by the OEM (mainly for the construction and agriculture markets).

### MAIN CHARACTERISTICS

	Units	Typical Value
Specific gravity at 20° C	kg/m <sup>3</sup>	868
Kinematic viscosity at 40° C	mm <sup>2</sup> /s	39
Kinematic viscosity at 100° C	mm <sup>2</sup> /s	7.8
Viscosity index		180
Pour point	° C	-42
Flash point Cleveland O.C.	° C	> 190

The data given in this table are typical values from production and cannot be specifications in any case.

### PROPERTIES & ADVANTAGES

- Viscosity adapted for the automatic transmissions requirements
- Very good anti-foam, anti-rust, anti-corrosion and anti-wear properties
- Non-aggressive onto the elastomers (seals) used in the modern transmissions
- High viscosity index
- Low pour point.
- High resistance to shear stress improving the performances in service

### SPECIFICATIONS

**DEXRON II D**  
**FORD MERCON (87)**  
**FORD M2C 166H**

**MAN 339 type D**  
**MB 236.6**  
**ZF TE ML 03D/04D/11A/14A and 17C**

