



L'huile des records du monde

BVX LS 200 – SAE 80W-90

High quality mineral oil for Limited Slip Differentials
Special for 4 WD vehicles

USES

Lubrication of **Limited Slip Differentials** of passenger cars, trucks, construction and agricultural equipment where a SAE 80W-90 LS product is recommended by the OEM.

Especially developed for Limited Slip Differentials of **4-WD vehicles**.

It may be used in classic differentials when an API GL-5 extreme-pressure oil is recommended.

MAIN CHARACTERISTICS

	Units	SAE 80W-90
Density at 20° C	kg/m ³	899
Kinematic viscosity at 40° C	mm ² /s	175
Kinematic viscosity at 100° C	mm ² /s	17.0
Viscosity index		103
Pour point	° C	- 30
Flash point Cleveland Open Cup	° C	190

PROPERTIES & ADVANTAGES

- **Specific** formulation with friction modifiers
- Good fluidity at cold temperatures
- Very good protection against rust and corrosion
- High multigrade properties
- Efficient protection of the hypoid gears
- No chattering of the friction system
- **Rapid oil flow during cold weather start-up**
- High thermal stability

PERFORMANCES

API GL5, LS

HOMOLOGATIONS

ZF TE-ML 05C and 12C

BVX LS 200 largely exceeds the performances mentioned.