



L'huile des records du monde

BVX R 500 – SAE 75W-80

100% semi-synthetic high performance oil for manual transmissions

USES

Lubrication of modern manual transmissions and drive axles of passenger cars where a SAE 75W-80 grade is recommended by the OEM (especially **Peugeot, Citroen, Renault**).

Particularly recommended for extended course of severe service, any driving conditions (motorway city traffic), any season.

MAIN CHARACTERISTICS

| | Units | SAE 75W-80 |
|--------------------------------|--------------------|------------|
| Density at 20° C | kg/m ³ | 872 |
| Kinematic viscosity at 40° C | mm ² /s | 43 |
| Kinematic viscosity at 100° C | mm ² /s | 7.8 |
| Viscosity index | | 153 |
| Pour point | ° C | -45 |
| Flash point Cleveland open cup | ° C | 200 |

PROPERTIES & ADVANTAGES

- **100% semi synthetic** : formulated with half synthetic molecules and half mineral bases
- Excellent fluidity at low temperatures
- High extreme-pressure properties
- Excellent resistance to oxidation allowing an optimal lubrication till the drain
- Excellent lubricating protection of the gearbox components. Easier cold weather start-up and energy saving capabilities

PERFORMANCES

API GL-5

BVX R 500 exceeds the performances mentioned.