



L'huile des records du monde

BVX Z-500 – SAE 75W-80

100% semi-synthetic oil for manual gear boxes with or without Intarder

USES

For lubrication of manual gear boxes when an **API GL4 SAE 75W-80 grade** is required.

Allows longer interval between two drains and improves fuel economies.

Recommended for truck gear boxes **with or without intarder** for any kind of driving (city, road, highways) whatever the seasons are and in **severe driving conditions**.

MAIN CHARACTERISTICS

	Units	SAE 75W-80
Density at 20° C	kg/m ³	876
Kinematic viscosity at 40° C	mm ² /s	60
Kinematic viscosity at 100° C	mm ² /s	9,1
Viscosity index		128
Pour point	° C	-45
Flash Point Open Cup	° C	200

PROPERTIES & ADVANTAGES

- **100% semi-synthetic** for a better resistance of the oil against thermal degradation and oxidation.
- Excellent fluidity at low temperature.
- High extreme-pressure properties.
- Warranties long life to gear boxes allowing a longer interval between 2 oil drains.
- Improves the gear shifting even if the engine is cold and allows fuel economy.
- Excellent lubricating power for a better protection of the boxes.

HOMOLOGATIONS

ZF TE ML-02D
MAN 341 TL
EATON LONG DRAIN

SPECIFICATIONS

API GL4, MIL.L.2105
DAF* , IVECO* , RENAULT V.I.*

BVX Z-500 SAE 75W80 widely exceeds the performances here -above mentioned

*According to the type of the box and the manufacturer requirements.

