



L'huile des records du monde

INBOARD 100 4T DIESEL SAE 15W40

High range Mineral oil for 4 stroke inboard Diesel engines

USES

Mineral oil especially created for 4 stroke inboard Diesel engines of pleasure boats and fishing boats (sea costs and river ones).

MAIN CHARACTERISTICS

		UNITS	Typical Values
Density at	20° C	kg/m ³	884
Kinematic Viscosity at	40° C	mm ² /s	115
Kinematic viscosity at	100° C	mm ² /s	14.7
Viscosity index			131
Dynamic viscosity at	- 20°C	mPa.s	6500
TBN (Total Base Number)		mg KOH/g	10.2
Flash Point Cleveland open cup		° C	> 200

The data given in this table are typical values from production and cannot be specifications in any case

PROPERTIES & ADVANTAGES

- Specific additivation developed for severe service conditions and high temperatures.
- Optimised performance to insure an excellent protection against wear and to prevent cylinder wear.
- Very good behaviour to oxidation allowing long intervals between two drains.
- Formulated for recent and depolluted engines (EURO 3, EURO 4 norms without PDF), this oil is convenient for any Diesel engine with or without a turbo.

HOMOLOGATIONS

BAUDOUIIN service 5*
VOLVO VDS-3
MTU type 2

SPECIFICATIONS

API CI-4 / CH-4 ; ACEA E7
Cummins CES 20078/20077/20076
MAN M 3275
Mercedes-Benz DC 228.3

INBOARD 100 4T DIESEL widely exceeds the performances indicated by **API** and by the **manufacturers**.

* For engines of the M26SR range with P1 and P2 adjustments and with a sulfur content in the fuel lower than 0.2 %

