



L'huile des records du monde

# MARINE 35– SAE 15W-40

High range mineral oil for diesel marine engines

## USES

**S.H.P.D.** oil created to be in conformance with the requirements of diesel engines, specific to the professional marine.

It is convenient for all the diesel engines with little emissions (according to the **EURO 2** norm).

It is well adapted to the turbo compressed engines used in **severe conditions, whatever the season is.**

## MAIN CHARACTERISTICS

		UNITS	SAE 15W 40
Density at	20° C	kg/m <sup>3</sup>	885
Kinematic Viscosity at	40° C	mm <sup>2</sup> /s	105
Kinematic viscosity at	100° C	mm <sup>2</sup> /s	14.4
Viscosity index			141
Dynamic viscosity at	- 20°C	mPa.s	6200
Pour Point		° C	-30
Flash point Cleveland open cup		°C	220
T.B.N. (Total Base Number)		mgKOH/g	15

## PROPERTIES & ADVANTAGES

- Very good resistance to oxidation
- Very high levels of **detergency and dispersivity**
- Keeping of **rheology characteristics** when in service.
- Prevents jacket polishing.
- Reinforced **antiwear** protection.
- Longer drain intervals according to the manufacturer recommendations.

## PERFORMANCES

API CF

VOLVO VDS  
BAUDOUIN service 4