



L'huile des records du monde

MVX 1000 2T

100% synthetic oil for 2-stroke motorbikes, karting, Quads and U.L.M. engines

USES

MVX 1000 2T has been specially **formulated and tested** in competition for the lubrication of 2-stroke engines, with very **high output and working speed**.

Is also adapted to the lubrication of new 2-stroke engines with direct injection system. Suitable for **separated greasing or premix systems**.

Mixture : according to the manufacturers' recommendations ; generally 2 %, up to 6 % for 100 cm³ kartings.

MAIN CHARACTERISTICS

	Units	Typical Values
Density at 20° C	kg/m ³	879
Kinematic viscosity at 40° C	mm ² /s	74.4
Kinematic viscosity at 100° C	mm ² /s	11.7
Viscosity index		152
Pour point	° C	-54
Flash Point Cleveland open cup	° C	94
Color		Blue

The data given in this table are typical values from production and cannot be specifications in any case.

PROPERTIES & ADVANTAGES


- Exceptional resistance to **high temperatures**, due to synthetic ester basis
- Excellent **anti-smoke** performances
- Pre-diluted oil for easier and quick fuel/oil mixture.
- Low ash percentage, yielding no deposits in the combustion chamber
- **Reduces exhaust system clogging**, lights and piston scaling

PERFORMANCES

API TC
ISO-L-EGD (Reinforced detergency/ API TC)

HOMOLOGATIONS

JASO FC



MVX 1000 2T exceeds the requirements here-above mentioned.

