



L'huile des records du monde

MVX 1000 4T – SAE 10W-50

100 % synthetic oil for 4 stroke motorbike and quad engines

USES

MVX 1000 4T is specially **studied and developed** to lubricate solicited 4 stroke engines : long distances, enduro, trial.

Also suitable for integrated gearboxes.

MAIN CHARACTERISTICS

		Units	SAE 10W-50
Density	20° C	kg/m ³	856
Kinematic viscosity	40° C	mm ² /s	126
Kinematic viscosity	100° C	mm ² /s	18.3
Viscosity Index			163
Pour Point		° C	-48
Flash Point Cleveland open cup		° C	216
Dynamic viscosity	-25° C	mPa.s	4900

PROPERTIES & ADVANTAGES

- Excellent stability at **high temperature**
- **Quick lubrication** as soon as we start the engine
- Use of viscosity index improves allowing an exceptional **shear stability**
- Keeps the engine, gear box and gearing system performances
- Reduces fuel consumption and exhaust soot emission
- Low volatility to reduce oil consumption
- High friction coefficient in accordance with the JASO MA requirements

HOMOLOGATION

JASO MA



SPECIFICATION

API SJ

Tested and approved in competition, **MVX 1000 4T widely exceeds** the performances required by the major OEM and in particular by the Japanese standard JASO MA and the american standard API SJ.

