



L'huile des records du monde

MVX 500 4T – SAE 10W-40

100 % semi synthetic oil for 4 stroke motorbike engines

USES

MVX 500 4T is adapted to lubricate engines working under **severe conditions** and **anytime** in the year : cross, city, road, motorway.

Suitable for integrated gearboxes, and miscible with the lubricants of the same category.

MAIN CHARACTERISTICS

		Units	SAE 10W-40
Density	20° C	kg/m ³	870
Kinematic viscosity	40° C	mm ² /s	102
Kinematic viscosity	100° C	mm ² /s	15
Viscosity Index			154
Pour Point		° C	-33
Flash Point Cleveland open cup		° C	222
Dynamic viscosity	-25° C	mPa.s	5800

PROPERTIES & ADVANTAGES

- Grade SAE 10W40 improving **cold starts**
- **Quick lubrication** when starting the engine
- Good levels of detergency and dispersivity
- Well adapted friction properties allowing a very good working of gearing
- Excellent protection against **wear**
- Keeps on the initial engine performances because of a **good protection against deposit formation**
- Reduces the **fumes exhaust and fuel consumption**

SPECIFICATIONS

API SJ

Engine performance and friction tests are in accordance with JASO MA Norm.

MVX 500 4T SAE 10W-40 exceeds the most severe requirements of the major manufacturers.