



L'huile des records du monde

MVX 500 4T – SAE 15W-50

100 % semi synthetic oil for 4 stroke motorbike engines

USES

MVX 500 4T is particularly adapted to lubricate engines working **under very severe conditions** : cross, city (traffic jam), road, motorway.

Suitable for integrated gearboxes, and miscible with the lubricants of the same category.

MAIN CHARACTERISTICS

| | | Units | SAE 15W-50 |
|--------------------------------|--------|--------------------|------------|
| Density | 20° C | kg/m ³ | 877 |
| Kinematic viscosity | 40° C | mm ² /s | 137 |
| Kinematic viscosity | 100° C | mm ² /s | 18.1 |
| Viscosity Index | | | 148 |
| Pour Point | | ° C | -30 |
| Flash Point Cleveland open cup | | ° C | 228 |
| Dynamic viscosity | -20° C | mPa.s | 6500 |

PROPERTIES & ADVANTAGES

- Grade SAE 15W50 for an **excellent lubrication at very high temperatures**
- Good levels of **detergency and dispersivity**
- Very good friction properties **preventing the « gear sliding » phenomenon**
- Very good protection against **wear**
- **Keeps the engine clean** allowing the removal of pollution during the oil drain
- **Low volatility** which reduces oil consumption

SPECIFICATIONS

API SJ

Engine performance and friction tests are in accordance with JASO MA Norm.

MVX 500 4T SAE 15W-50 exceeds the most severe requirements of the major manufacturers.