



L'huile des records du monde

# MVX SCOOT 2T

100% semi-synthetic oil for 2-stroke Scooter engines

## USES

MVX SCOOT 2T has been specially studied and is recommended for the lubrication of 2-stroke scooter engines, used down-town, or on roads under severe conditions.

*For scooters equipped with direct injection systems, use YACCO MVX 1000 2T*

Suitable for separated greasing or premix systems.

Mixture : from 2 to 4 %, depending on the OEM requirements.

## MAIN CHARACTERISTICS

	Units	Typical values
Density at 20° C	kg/m <sup>3</sup>	872
Kinematic viscosity at 40° C	mm <sup>2</sup> /s	74
Kinematic viscosity at 100° C	mm <sup>2</sup> /s	10.5
Viscosity index		129
Pour Point	° C	-33
Flash Point Cleveland open cup	° C	102

The data given in this table are typical values from production and cannot be specifications in any case.

## PROPERTIES & ADVANTAGES


- Optimal lubrication at **high temperatures**
- Very good **anti-smoke** performances
- Prevents sparkplug problem and piston ring gumming
- **Permanent oil film strenght**
- The pre-diluted oil allows a quick mixing with the fuel

## PERFORMANCES

API TC  
ISO-L-EGD

## HOMOLOGATIONS

JASO FC



MVX SCOOT 2T exceeds the requirements here-above mentioned.

