



L'huile des records du monde

TRANSPRO 25 - SAE 15W-40

Mineral oil for Diesel engines of heavy-duty trucks

USES

This high performance mineral oil meets the requirements of Euro 2 Diesel engines and some older engines turbo-charged or not . This oil is suitable for heavy-duty trucks, construction and agricultural equipment and industrial engines (generating sets, ...)

Also suitable for certain models of marine engines and some Gasoline engines.

Its performances and the SAE 15W-40 grade allow the use in Diesel engines, turbo-charged or not, used under severe service conditions all year round.

MAIN CHARACTERISTICS

		Units	15W-40
Density at	20° C	kg/m ³	878
Kinematic viscosity at	40° C	mm ² /s	106
Kinematic viscosity at	100° C	mm ² /s	14.5
Viscosity Index			140
Pour Point		° C	-30
Flash Point Cleveland open cup		° C	> 200
Dynamic viscosity at	-20° C	mPa.s	6400

The data given in this table are typical values from production and cannot be specifications in any case.

PROPERTIES & ADVANTAGES

- High thermal and mechanical stability
- Extended oil drain intervals up to 30.000 km, according to the service conditions and the OEM recommendations
- Remarkable anti-wear and anti-corrosion properties
- Maintains optimal performances all season
- Remains free of sludge, varnish and other by-products of high temperature degradation

SPECIFICATIONS

API CG-4/CF -4/SJ
ACEA E2
ALLISON C4
CATERPILLAR TO2
M.T.U. type 1

HOMOLOGATIONS

MAN 271
MB-Approval 228.1
VOLVO VDS

