



L'huile des records du monde

## TRANSPRO 25 - SAE 20W-50

Mineral oil for Diesel engines of heavy-duty trucks

### USES

This high performance mineral oil meets the requirements of heavy-duty trucks Diesel engines turbo-charged or not, agricultural and construction heavy equipment.

Also suitable for certain models of marine engines and Gasoline engines.

Its polyvalent properties allow a good lubrication and particularly an optimal protection for hot climates.

### MAIN CHARACTERISTICS

		Units	20W-50
Density at	20° C	kg/m <sup>3</sup>	890
Kinematic viscosity at	40° C	mm <sup>2</sup> /s	168
Kinematic viscosity at	100° C	mm <sup>2</sup> /s	18.3
Viscosity Index			121
Pour Point		° C	-21
Flash Point Cleveland open cup		° C	236
Dynamic viscosity at	-15° C	mPa.s	8800

*The data given in this table are typical values from production and cannot be specifications in any case.*

### PROPERTIES & ADVANTAGES

- High thermal and mechanical stability
- Outstanding anti-wear and anti-corrosion properties
- Extended oil drain intervals up to 30.000 km, according to the service conditions and the OEM recommendations
- The SAE 50 grade provides excellent performance at high temperature.
- Its resistance to volatility keeps oil consumption extremely low

### SPECIFICATIONS

API CG-4/CF -4/SJ  
ACEA E2  
ALLISON C4

MAN 271  
MB 228.1  
M.T.U. type 1  
VOLVO VDS

