



L'huile des records du monde

YASOLVANE

Degreaser, in cold conditions

USES

Formulated to degrease and clean the engines, the mechanical parts and the industrial floors **in cold conditions**.

! : Not for use when hot.

MAIN CHARACTERISTICS

	Values
Density at 20°C (Kg/m ³)	787
Aspect	Fluid Liquid
Colour	Light yellow
Smell	Light
Flash point Cleveland open cup °C	68

The data given in this table are typical values from production and cannot be specifications in any case.

PROPERTIES & ADVANTAGES

- Good wettability, detergency and dispersancy and emulsion properties
- “Milky” emulsion in case of water content.
- Degreaser in cold conditions (**absolutely forbidden to use it in hot conditions**)
- Lightly inflammable in normal conditions of use.

DIRECTIONS

- Small mechanical parts

Plunge 15 min. in the pure product, brush, rinse with water then dry with comp' air

- Big mechanical parts

Spray the pure product, let it penetrate during 15 to 20 min., brush if necessary then rinse.

- Passenger cars, agricultural or pleasure boats engines

Protect electrical circuit with plastic films, then apply with a brush or spray the pure product, let it operate for 15 to 20 min., rinse with water then dry with comp' air

CAUTION USE

Noxious product. Before using it, please read the safety label on the packaging and/or check the Health and Safety Sheet available on yacco-lub.com.

Do not use on grease remover machines built to use alkaline soaps.